

Downlight

DWC536.37-SF-C-40W

Picture



Packing

UnitVolum (CBM)	0,0036465
Unit GW (kg)	1,27
Qty per carton	10

Description

Type	LED Downlight
Connection	Wire

Electrical Parameters

Gr. Power	40W ±5%
InputVoltage	AC220-240V
Driver	DONE; Lifud
Dimmable	Not dim.

Lighting Parameters

Beam Angle	15/30/45
Colors	2700°K; 3000°K; 4000°K; 5000°K;
Lumens	3200
CRI	80Ra

Structure Parameters

Fixture Color	White; Black
Cover	Lens
Dimensions	536*37*86mm

Protection Parameters

Rating	Indoor Use/UGR<19
Electrical Class	Class I <input type="checkbox"/> Class II <input checked="" type="checkbox"/> Class III <input type="checkbox"/>
Lifetime	>50.000h
Warranty (Years)	2

Options

Dimmable	Triac <input type="checkbox"/> 0-10V <input type="checkbox"/> 1-10V <input type="checkbox"/> DALI <input type="checkbox"/>
CRI	>90Ra <input checked="" type="checkbox"/> >92Ra <input type="checkbox"/> >95Ra <input checked="" type="checkbox"/> >98Ra <input type="checkbox"/>
Other	Pendant or Surface mounting accessories