

DWC85.85-DR1-C-12W



Source	LED Osram; Cree; Bridgelux
Connection	Wire
Gr. Power	12W $\pm$ 5%
Input Voltage	AC85-277V
Driver	Kegu; Lifud
Control (standard)	Not dim.
Dimming option	Triac dim.; 0-10V dim.; DALI
Beam Angle (°)	15/24/36
CCT (Kelvins)	2700°K; 3000°K; 4000°K; 5000°K; 6500°K; 5700°K
Lumens	1150-1250
Luminaire efficiency	104Lm/W
CRI (standard)	>80Ra
for option	>90Ra; >97Ra
Fixture Color	White; Black; White+Black
Cover	Lens; Louver
Dimensions	A85*B62*C75mm
Protection Rating	Indoor Use
Electrical Class	Class II
Lifetime	>50.000h
Warranty	3 Years

Standard Packing Details


Unit Volum (CBM)	0,00102
Unit GW (kg)	0
Qty per carton	27

Other

for option: louver; flicker free driver; White frame + black reflector

DWC85.85-DR1-C-12W

Sizes drawing




DWC85.85-DR1-C-12W.drw

in mm

Illumination Diagram

1250Lm with 24° beam



DWC85.85-DR1-C-12W.lux

