

Surface Downlight

DWR140-MC-SF-C-40W



Source	LED Osram; Cree; Bridgelux; Citize
Connection	Wire
Gr. Power	30W ±5%
Input Voltage	AC85-277V
Driver	Kegu; Lifud
Control (standard)	Not dim.
Dimming option	Triac dim.; 0-10V dim.; DALI
Beam Angle (°)	45
CCT (Kelvins)	2700°K; 3000°K; 4000°K; 5000°K; 6500°K; 5700°K
Lumens	3900-4100
Luminaire efficiency	137Lm/W
CRI (standard)	>80Ra
for option	>90Ra; >97Ra
Fixture Color	White; Black
Cover	Clear; Louver
Dimensions	Dia142*B160mm
Protection Rating	Indoor Use
Electrical Class	Class II
Lifetime	>50.000h
Warranty	3 (Years)

Standard Packing Details

Unit Volum (CBM)	0,00395
Unit GW (kg)	0
Qty per carton	18


Other

Flicker free driver; Tridonic or Philips Driver; Reflector cup: Black, White, Chrome, Brushed Nickel, Brushed Brass

Surface Downlight

DWR140-MC-SF-C-40W

Sizes drawing




DWR140-MC-SF-C-40W.drw

in mm

Illumination Diagram

4100Lm with 45° beam



DWR140-MC-SF-C-40W.lux

Reflector

- W White
- B Black
- CH Chrome
- BN Brushed Nickel
- BB Brushed Brass